



IT / Medical Open Frame Power Supply 200 Watt Series

ATM200T-F X X X

→ O / P Voltage

Green Mode

Meet CEC, DoE Level VI, ErP Stage 2
No Load Power Consumption Less Than 0.21W

Features :

- ANSI/AAMI/IEC/EN ES60601-1:2012 (60601 Edition 3.1)
- Means of Protection: 2 X MOPP
- Touch Current : < 100μA
- Meet IEC/EN/UL 60950-1
- 100-240VAC Universal Input
- Single Output to 200W
- Regulated Output With Low Ripple Noise
- Modified and Custom Design Available
- 2 Years Warranty

Model	O/P Voltage	O/P Current	Watt
ATM200T-F120	12.0V	16.00A	192W
ATM200T-F190	19.0V	10.50A	200W
ATM200T-F240	24.0V	8.30A	200W
ATM200T-F360	36.0V	5.50A	200W
ATM200T-F480	48.0V	4.20A	200W

Input

Voltage	100-240VAC
Line Frequency	50-60Hz
Current	2.5A-0.9A
Protection	Internal Primary Current Fuse

Output

Load Regulation	±5% (Typical)
Ripple & Noise	1% Vp-p Max. for Output Voltage@ Full Load
Transient Response	0.5mS for 50% Load Change Typical
Hold-up Time	10mS @ Full Load
Protection	Short Circuit Protection / Over Voltage Protection / Over Current Protection / Over Temperature Protection

Safety Approvals

CB / UL / cUL / T-mark(TÜV)

Electrical

Topology	LLC
Dielectric Withstand	4000VAC Primary - Secondary
Touch Current	< 100μA
MTBF	300,000 Calculated Hours at 25°C , by Telcordia SR-332

Environmental

Operating Temperature	0 to + 50°C
Storage Temperature	-20 to + 80°C
Relative Humidity	Operating : 20 to 80% RH Storage : 10 to 90% RH
Cooling	Natural Convection Cooling

Mechanical

Dimension	L127 × W76.2 × H38.1 (mm) 5" x 3" x 1.5" (inch)
Weight	320g (Ref.)